

EGCO®

Gemineye™
CAMERA / DATA STORAGE SYSTEM



CAMERA SYSTEMS

Beacons | Lightbars | Minibars | Directional LEDs | Worklamps | Back-Up Alarms

K7000B 7.0" LCD Color System

Comprising a feature-packed 7.0" LCD high-resolution color monitor with internal controller and CMOS infrared color camera, the K7000B delivers excellent picture quality even in low-light conditions. The compact monitor includes a sunshade, remote control and allows for unobtrusive installation without compromising viewable screen area. System is expandable up to 2 cameras*.

Specifications

PART NO.	M7000B Monitor	C2013B Camera
Image	7.0" LCD Monitor	1/4" CMOS Color NTSC 580H x 492V Pixels
Voltage	12/24 VDC	-
Consumption	<5W	<1W
Lens	-	2.9mm
Lens Angle	-	120° Diagonal
Mirror Image	Yes (via menu select)	-
Audio	No	No
Light Sensor	No	Auto Switch B&W
Infrared LEDs	-	18 (10-12m visibility)
Contrast/Bright	Yes	-
Camera Selection	1-2 (via trigger wire)	-
Housing	Plastic	Aluminum Alloy
Mechanical Vibration	-	6G
Mounting	Permanent	Tilt Bracket
Weight	0.88 LBS	0.60 LBS
Dimensions	6.85"W x 4.49"H x 0.94"D	2.92"W x 3.01"H x 2.62"D
Temperature	-4°F to +158°F	-22°F to +158°F
Certification	FCC, CE, RoHS	IP69K, FCC, CE, RoHS
Connection	9 Pin Female Y Harness (supplied) 9 Pin Male 4 Pin Female Threaded x 2	4 Pin Male Threaded

System Expansion Options

- Camera - 1 Additional: C2013B



- Cable: DAC1016



* Kit includes a short Y type wiring harness

Distribution in Switzerland:
Comax Industrielle Signaltechnik AG
Römerstrasse 6, CH-4512 Bellach
Tel: +41 32 617 31 41
mail@comax.ch www.comax.ch

alarmiert, warnt, ruft, meldet
Comax