Electronic Alarm Horn with LED signal light H₁₀₀TL

Comax Signaltechnik




General information

Universal electronic alarm horn with trumpet and LED signal light for manifold uses. Three different tones selectable. Volume control. LED signal light in 6 different colours. Separate control of horn or LED signal light. Large range of tensions in AC and DC. High degree of protection IP65.

	121.1	
		4.050
43	100.2	

Technical data		
Case	ABS, shock-resistant	
Colour of case	light grey	
Lens	PC, shock-resistant	
Colours of lens/LED	red, amber, blue, green, yellow, clear	
Output	5,5cd (amber LED/lens)	
Degree of protection	IP65 according to EN60529	
Temperature range	-25°C to +50 °C	
Duty cycle	continuous operation	
LED signal light	continuous light, 9 high power LED	
Tones	buzzer	
	alternate tone 1200/500Hz, 1Hz	
	alternate tone 800/1000Hz, 7Hz	
Connection		
- cable entry	5-7mm Ø push-through grommet	
- cable installation	flush or surface mounting	
- lead	terminal up to 0,5 - 1,5mm ²	
Weight	approx. 0.215 kg	



Item number	Rated voltage	Sound intensity level	Current consumption	Type
H100TL.024.2*	12-30VDC	approx. 100dB(A), 1m	horn: 24mA at 24VDC	with trumpet
			LED: 80mA at 24VDC	•
H100TL.230.7*	90-260VAC	approx. 100dB(A), 1m	horn: 10mA at 230VAC	with trumpet
			LED: 32mA at 230VAC	·

1= red, 2= amber, 3= yellow, 4= green, 5= blue, 7 = clear

Subject to change without prior notice



